

# FEIDER



## FOLDABLE POLE DRYWALL SANDER **FPG7202P** USER GUIDE

CAUTION: Read the instruction manual before using this product!

# CONTENTS

|                                   |    |
|-----------------------------------|----|
| 1. SAFETY INSTRUCTIONS.....       | 3  |
| 2. YOUR PRODUCT.....              | 7  |
| 3. OPERATION.....                 | 9  |
| 4. MAINTENANCE AND STORAGE.....   | 12 |
| 5. DISPOSAL.....                  | 12 |
| 6. DECLARATION OF CONFORMITY..... | 13 |
| 7. WARRANTY.....                  | 14 |
| 8. PRODUCT FAILURE.....           | 15 |
| 9. WARRANTY EXCLUSIONS.....       | 16 |

# 1. SAFETY INSTRUCTIONS

## General Power Tool Safety Warnings

**⚠️ WARNING!** Read all safety warnings and all instructions, illustrations and specifications provided with this power tool. *Failure to follow all instructions listed below may result in electric shock, fire and/or serious injury.*

**Save all warnings and instructions for future reference.** The term "power tool" in the warnings refers to your mains-operated (corded) power tool or battery-operated (cordless) power tool.

### 1) Work area safety

- a) **Keep work area clean and well lit.** *Cluttered or dark areas invite accidents.*
- b) **Do not operate power tools in explosive atmospheres, such as in the presence of flammable liquids, gases or dust.** *Power tools create sparks which may ignite the dust or fumes.*
- c) **Keep children and bystanders away while operating a power tool.** *Distractions can cause you to lose control.*

### 2) Electrical safety

- a) **Power tool plugs must match the outlet. Never modify the plug in any way. Do not use any adapter plugs with earthed (grounded) power tools.** *Unmodified plugs and matching outlets will reduce risk of electric shock.*
- b) **Avoid body contact with earthed or grounded surfaces, such as pipes, radiators, ranges and refrigerators.** *There is an increased risk of electric shock if your body is earthed or grounded.*
- c) **Do not expose power tools to rain or wet conditions.** *Water entering a power tool will increase the risk of electric shock.*
- d) **Do not abuse the cord. Never use the cord for carrying, pulling or unplugging the power tool. Keep cord away from heat, oil, sharp edges or moving parts.** *Damaged or entangled cords increase the risk of electric shock.*
- e) **When operating a power tool outdoors, use an extension cord suitable for outdoor use.** *Use of a cord suitable for outdoor use reduces the risk of electric shock.*
- f) **If operating a power tool in a damp location is unavoidable, use a residual current device (RCD) protected supply.** *Use of an RCD reduces the risk of electric shock.*

### 3) Personal safety

- a) **Stay alert, watch what you are doing and use common sense when operating a power tool. Do not use a power tool while you are tired or under the influence of drugs, alcohol or medication.** *A moment of inattention while operating power tools may result in serious personal injury.*
- b) **Use personal protective equipment. Always wear eye protection.** *Protective equipment such as dust mask, non-skid safety shoes, hard hat, or hearing protection used for appropriate conditions will reduce personal injuries.*
- c) **Prevent unintentional starting. Ensure the switch is in the off-position before connecting to power source and/or battery pack, picking up or carrying the tool.** *Carrying power tools with your finger on the switch or energising power tools that have the switch on invites accidents.*

- d) **Remove any adjusting key or wrench before turning the power tool on.** *A wrench or a key left attached to a rotating part of the power tool may result in personal injury.*
- e) **Do not overreach. Keep proper footing and balance at all times.** *This enables better control of the power tool in unexpected situations.*
- f) **Dress properly. Do not wear loose clothing or jewellery. Keep your hair, clothing and gloves away from moving parts.** *Loose clothes, jewellery or long hair can be caught in moving parts.*
- g) **If devices are provided for the connection of dust extraction and collection facilities, ensure these are connected and properly used.** *Use of dust collection can reduce dust-related hazards.*
- h) **Do not let familiarity gained from frequent use of tools allow you to become complacent and ignore tool safety principles.** *A careless action can cause severe injury within a fraction of a second.*

#### 4) **Power tool use and care**

- a) **Do not force the power tool. Use the correct power tool for your application.** *The correct power tool will do the job better and safer at the rate for which it was designed.*
- b) **Do not use the power tool if the switch does not turn it on and off.** *Any power tool that cannot be controlled with the switch is dangerous and must be repaired.*
- c) **Disconnect the plug from the power source and/or the battery pack from the power tool before making any adjustments, changing accessories, or storing power tools.** *Such preventive safety measures reduce the risk of starting the power tool accidentally.*
- d) **Store idle power tools out of the reach of children and do not allow persons unfamiliar with the power tool or these instructions to operate the power tool.** *Power tools are dangerous in the hands of untrained users.*
- e) **Maintain power tools. Check for misalignment or binding of moving parts, breakage of parts and any other condition that may affect the power tool's operation. If damaged, have the power tool repaired before use.** *Many accidents are caused by poorly maintained power tools.*
- f) **Keep cutting tools sharp and clean.** *Properly maintained cutting tools with sharp cutting edges are less likely to bind and are easier to control.*
- g) **Use the power tool, accessories and tool bits etc. in accordance with these instructions, taking into account the working conditions and the work to be performed.** *Use of the power tool for operations different from those intended could result in a hazardous situation.*
- h) **Keep handles and grasping surfaces dry, clean and free from oil and grease.** *Slippery handles and grasping surfaces do not allow for safe handling and control of the tool in unexpected situations.*

#### 5) **Service**

- a) **Have your power tool serviced by a qualified repair person using only identical replacement parts.** *This will ensure that the safety of the power tool is maintained.*

#### **Safety instructions for all operations**

#### **Safety Warnings Common for Grinding, Sanding, Wire Brushing, Polishing or Abrasive Cutting-Off Operations**

- a) **This power tool is intended to function as a sander. Read all safety warnings, instructions, illustrations and specifications provided with this power tool. *Failure to follow all instructions listed below may result in electric shock, fire and/or serious injury.***
- b) **Operations such as grinding, wire brushing, polishing or cutting-off are not recommended to be performed with this power tool. *Operations for which the power tool was not designed may create a hazard and cause personal injury.***
- c) **Do not use accessories which are not specifically designed and recommended by the tool manufacturer. *Just because the accessory can be attached to your power tool, it does not assure safe operation.***
- d) **The rated speed of the accessory must be at least equal to the maximum speed marked on the power tool. *Accessories running faster than their rated speed can break and fly apart.***
- e) **The outside diameter and the thickness of your accessory must be within the capacity rating of your power tool. *Incorrectly sized accessories cannot be adequately guarded or controlled.***
- f) **Threaded mounting of accessories must match the grinder spindle thread. For accessories mounted by flanges, the arbour hole of the accessory must fit the locating diameter of the flange. *Accessories that do not match the mounting hardware of the power tool will run out of balance, vibrate excessively and may cause loss of control.***
- g) **Do not use a damaged accessory. Before each use inspect the accessory such as abrasive wheels for chips and cracks, backing pad for cracks, tear or excess wear, wire brush for loose or cracked wires. If power tool or accessory is dropped, inspect for damage or install an undamaged accessory. After inspecting and installing an accessory, position yourself and bystanders away from the plane of the rotating accessory and run the power tool at maximum no-load speed for one minute. *Damaged accessories will normally break apart during this test time.***
- h) **Wear personal protective equipment. Depending on application, use face shield, safety goggles or safety glasses. As appropriate, wear dust mask, hearing protectors, gloves and workshop apron capable of stopping small abrasive or workpiece fragments. *The eye protection must be capable of stopping flying debris generated by various operations. The dust mask or respirator must be capable of filtering particles generated by your operation. Prolonged exposure to high intensity noise may cause hearing loss.***
- i) **Keep bystanders a safe distance away from work area. Anyone entering the work area must wear personal protective equipment. *Fragments of workpiece or of a broken accessory may fly away and cause injury beyond immediate area of operation.***
- j) **Hold the power tool by insulated gripping surfaces only, when performing an operation where the cutting accessory may contact hidden wiring or its own cord. *Cutting accessory contacting a "live" wire may make exposed metal parts of the power tool "live" and could give the operator an electric shock.***
- k) **Position the cord clear of the spinning accessory. *If you lose control, the cord may be cut or snagged and your hand or arm may be pulled into the spinning accessory.***
- l) **Never lay the power tool down until the accessory has come to a complete stop. *The spinning accessory may grab the surface and pull the power tool out of your control.***
- m) **Do not run the power tool while carrying it at your side. *Accidental contact with the spinning accessory could snag your clothing, pulling the accessory into your body.***

- n) **Regularly clean the power tool's air vents.** *The motor's fan will draw the dust inside the housing and excessive accumulation of powdered metal may cause electrical hazards.*
- o) **Do not operate the power tool near flammable materials.** *Sparks could ignite these materials.*
- p) **Do not use accessories that require liquid coolants.** *Using water or other liquid coolants may result in electrocution or shock.*

### **Further safety instructions**

#### **Kickback and Related Warnings**

Kickback is a sudden reaction to a pinched or snagged rotating wheel, backing pad, brush or any other accessory. Pinching or snagging causes rapid stalling of the rotating accessory which in turn causes the uncontrolled power tool to be forced in the direction opposite of the accessory's rotation at the point of the binding.

For example, if an abrasive wheel is snagged or pinched by the workpiece, the edge of the wheel that is entering into the pinch point can dig into the surface of the material causing the wheel to climb out or kick out. The wheel may either jump toward or away from the operator, depending on direction of the wheel's movement at the point of pinching. Abrasive wheels may also break under these conditions.

Kickback is the result of power tool misuse and/or incorrect operating procedures or conditions and can be avoided by taking proper precautions as given below.

- a) **Maintain a firm grip on the power tool and position your body and arm to allow you to resist kickback forces.** *Always use auxiliary handle, if provided, for maximum control over kickback or torque reaction during start-up. The operator can control torque reactions or kickback forces, if proper precautions are taken.*
- b) **Never place your hand near the rotating accessory.** *Accessory may kickback over your hand.*
- c) **Do not position your body in the area where power tool will move if kickback occurs.** *Kickback will propel the tool in direction opposite to the wheel's movement at the point of snagging.*
- d) **Use special care when working corners, sharp edges etc. Avoid bouncing and snagging the accessory.** *Corners, sharp edges or bouncing have a tendency to snag the rotating accessory and cause loss of control or kickback.*
- e) **Do not attach a saw chain woodcarving blade or toothed saw blade.** *Such blades create frequent kickback and loss of control.*

### **Additional safety instructions for sanding operations**

#### **Safety Warnings Specific for Sanding Operations:**

- a) **Do not use excessively oversized sanding disc paper. Follow manufacturers' recommendations, when selecting sanding paper.** *Larger sanding paper extending beyond the sanding pad presents a laceration hazard and may cause snagging, tearing of the disc or kickback.*

### **Warning symbol**



**WARNING** - To reduce the risk of injury, user must read instruction manual.

|                                                                                   |                                                                                 |
|-----------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
|   | Always wear ear protection                                                      |
|  | Always wear goggles                                                             |
|  | Always wear a breathing mask                                                    |
|  | In accordance with essential applicable safety standards of European directives |
|  | Class II product                                                                |

### **Residual risks**

Even if you use this product in accordance with all safety requirements, the potential risks of injury and damage remain. The following risks may arise in the structure and design of this product. Always be vigilant when using this product, so you can recognize and manage the risks rather.

There are harmful health consequences resulting from the emission of vibrations if the product is used for long periods or is not properly managed and properly maintained.

There is a risk of injury about the emission of dust and potential debris.

Risk of injuries to persons and their property due to flying objects


Harmful/toxic dust can arise from sanding (e.g. lead painted surfaces, woods, etc.). Contact with or inhalation of these dusts can endanger the health of operator and bystanders. When using this tool, always wear personal protective equipment, specifically a dust mask protection. When operating the tool, take a position where you will not be in contact with these dusts.

### **Intended use**

The drywall sander is designed for sanding walls and ceilings made of drywall or plaster. The sander provides superior finish and is faster than conventional finishing methods for both new construction and renovation work. Clean-up time is minimized by using an external vacuum cleaner attached to the sander.

## **2. YOUR PRODUCT**

### **a. Description**



|   |                |   |                     |   |           |
|---|----------------|---|---------------------|---|-----------|
| 1 | Sanding pad    | 4 | Speed adjuster      | 7 | Delta pad |
| 2 | Motor          | 5 | ON/OFF switch (I/O) |   |           |
| 3 | Foldable lever | 6 | Extend handle       |   |           |

The tool is provided with:

- A set of sandpaper (round sanding paper + delta sanding paper) (see below for the characteristics)
- 1 screwdriver and 1 Hex key
- 1 tube and adaptors for the connection to a collector dust
- Clips to attach the supply cord on the flexible tube

**NOTE: The collector dust/dust bag is no provided with this model. You must buy an appropriate one in specialized stores. Ask device to your retailer.**

#### b. Technical data

|                                                               |                                                                                                                                                               |
|---------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Voltage supply                                                | 230-240V~                                                                                                                                                     |
| Power                                                         | 710W                                                                                                                                                          |
| Frequency                                                     | 50Hz                                                                                                                                                          |
| Speed                                                         | 1000-2100/min                                                                                                                                                 |
| Protection class                                              | II                                                                                                                                                            |
| Disc Diameter                                                 | Ø225mm                                                                                                                                                        |
| Weight                                                        | 4.1kg                                                                                                                                                         |
| Sound pressure level                                          | Disc-type sander<br>LpA: 92.5dB(A) K=3 dB(A)<br>Orbital sander<br>LpA: 91.5dB(A) K=3 dB(A)                                                                    |
| Sound power level                                             | Disc-type sander<br>LwA: 100,5 dB(A) K= 3 dB(A)<br>Orbital sander<br>LwA: 99,5 dB(A) K= 3 dB(A)                                                               |
| Vibration emission value for disc type sander function        | Main handle: 4.684 m/s <sup>2</sup> , Uncertainty K = 1,5 m/s <sup>2</sup><br>Auxiliary handle: 3.358 m/s <sup>2</sup> , Uncertainty K = 1,5 m/s <sup>2</sup> |
| Vibration emission value for triangle orbital sander function | Main handle: 7.965 m/s <sup>2</sup> , Uncertainty K = 1,5 m/s <sup>2</sup><br>Auxiliary handle: 8.953 m/s <sup>2</sup> , Uncertainty K = 1,5 m/s <sup>2</sup> |

The impact of noise can cause damage to hearing.

Overall oscillation value determined according to EN 62841

Information:

- The declared vibration total values and the declared noise emission values have been measured in accordance with a standard test method and may be used for comparing one tool with another.
- The declared vibration total values and the declared noise emission values may also be used in a preliminary assessment of exposure.



#### **Warning!**

- The vibration and noise emissions during actual use of the power tool can differ from the declared values depending on the ways in which the tool is used especially what kind of workpiece is processed; and

- It is necessary to identify safety measures to protect the operator that are based on an estimation of exposure in the actual conditions of use (taking account of all parts of the operating cycle such as the times when the tool is switched off and when it is running idle in addition to the trigger time).

### 3. OPERATION

#### a. Selection of the sandpaper

The drywall sander is equipped with 6 pcs of sanding paper (80/100/120/150/180/240).


This abrasive is suitable for most applications. 120 and 240 abrasive discs are available for works requiring a smoother finish.

According to the material and grinding effect, choose the appropriate sandpaper.

| Material                               | Usage                                      | Sandpaper |
|----------------------------------------|--------------------------------------------|-----------|
| Pigment                                | Removal of pigment layer                   | 40        |
| Paint                                  | Removal of paint                           | 60        |
| Filling agent                          | Sanding pigment (such as finishing bottom) | 80        |
| Interstitial material                  | Removal of pickling, sanding residues      | 100       |
| Pigment layer drips and convex surface | Removal brushing marks                     | 120       |
| Flat bottom material                   | Good finished sanding for new painting     | 180-240   |

#### b. Replacement of sanding paper

Before installing the new paper, the wheel must be clear from dirt. Clean it by using a brush. The surface of the adhesive disc has a lint layer that can quickly and easily be installed flocking self-adhesive sandpaper. The sandpaper surface has to be pressed on the adhesive disc.



#### c. Installation of the pad (sanding and delta pad)

Push the two locking device localized on the side of the bracket. If already installed, remove the current pad by turning it a little. Install the pad and release the locking device. Check if the pad is well installed.

#### d. Connection to the dust collecting bag

It is recommended to connect a dust collection device to the machine. Make this connection as shown in the picture below.




You can attach the supply cord on the tube by using the provided clips.

**NOTE:** The collector dust/dust bag is no provided with this model. You must buy an appropriate one in specialized stores. Ask device to your retailer.

#### e. Installation


##### Foldable lever

- Release foldable lever
- Make the hook well connecting
- Lock foldable lever



##### Telescopic tube


Insert the telescopic pipe into the front pipe, adjust to the desired length, and turn the locking nut into the front plastic pipe and lock.



#### f. Starting and stopping

Make sure that the power supply voltage is the same as that indicated on the sander's nameplate and that the selector switch is off. Connect the sander to the power supply.

To start the sander, press its switch to ON (I).




Press this switch to turn the machine OFF (O).



#### **g. Speed setting**

The Drywall Sander is equipped with variable speed control. The speed is adjusted by turning the control knob. The control knob goes from "MIN" to "MAX".

Use the higher speed settings for fast removal of the exceeding. Use the lower speed settings to reduce the removal rate to have more precise control.



#### **h. Adjustment of the tube size**

Depending on the different grinding positions, the length of the machine can be adjusted between 1100-1800mm. Turn the lock nut counter clockwise to loosen, pull the hose to the correct length and then turn the lock nut clockwise to lock.



#### **i. Sanding**

The head of the sander the head can rotate in several directions, allowing the abrasive pad to fit the work surface. This allows the operator to sand the top, middle and bottom of a wall or ceiling bracket without changing position.

- Plug in and turn on the sander.
- Hold it with both hands, one on the tube and another on the additional handle at the back
- Place the sander slightly against the work surface (apply a slight pressure to align the sanding head with the work surface).
- Apply extra pressure to push the abrasive pad towards the work surface and move the sander to smooth the surface.
- Apply sufficient pressure to keep the abrasive pad flat against the work surface. Excessive pressure can cause micro scratches and damage the work surface.
- The sander must always be in motion when the abrasive pad is in contact with the work surface. Use a regular sweeping motion. Stopping the sander (on the work surface) or moving the sander may cause micro scratches and affect the uniformity of the work surface.

**NOTE: Do not allow the rotating abrasive pad to come into contact with sharp or sharp edges. Contact with sharp objects can severely damage the abrasive pad.**

## 4. MAINTENANCE AND STORAGE

**If the replacement of the supply cord is necessary, this has to be done by the manufacturer or his agent in order to avoid a safety hazard.**

Tools should always be clean, clean up debris and dust.



Always change the oil (gearbox, bearings) for proper operation.

Always check the power cord, plugs, switches to make sure the tools are faultless.

The power tools manufactured by the company undergo a strict quality inspection. If the machine is faulty, please consult the authorized service centre (SWAP) for repair.

### a. Carbon brushes replacement

When the carbon brush reaches its wear limit, replace with a new one. Use a screwdriver to unscrew the brush cover, remove the original carbon brush, place a new carbon brush and screw the brush cover.



### b. Repairs

There are no repairs to be provided by the user. For inspection and repair, return the tool directly to a qualified service.

### c. Storage

After use and cleaning, store your tool. Store the tool in a clean, dry place. The tool should be kept away from children and pets.

Avoid exposing the tool to direct sunlight.

## 5. DISPOSAL



**CAUTION!** This product has been marked with a symbol relating to removing electric and electronic waste. This means that this product shall not be discarded with household waste but that it shall be returned to a collection system which conforms to the European

WEEE Directive. Contact your local authorities or ask for advice on recycling. It will then be recycled or dismantled in order to reduce the impact on the environment. Electric and electronic equipment can be hazardous for the environment and for human health since they contain hazardous substances.



## 6. DECLARATION OF CONFORMITY



SODILOG SAS

4 RUE CURIE, CS 91617 68016 COLMAR CEDEX FRANCE

**States that the designated below machine:**

Product: FOLDABLE POLE DRYWALL SANDER

Model: FPG7202P

Serial number: 20260601696-20260601845

**Developed, designed and manufactured in accordance with the requirements of directives:**

Machinery Directive 2006/42/EC

EMC Directive 2014/30/EC

ROHS Directive (EU)2015/863 amending 2011/65/EU

**Also meets the following standards:**

EN 62841-1: 2015/A11: 2022

EN IEC 62841-2-3: 2021/A11: 2021

EN 62841-2-4: 2014

EN IEC 55014-1: 2021

EN IEC 55014-2: 2021

EN IEC 61000-3-2: 2019/A1: 2021

EN61000-3-3: 2013/A2: 2021

Responsible of the technical file: Mark Z

COLMAR CEDEX, 15/06/2026

Jacques Masson/PDG

## 7. WARRANTY

The manufacturer guarantees the product against defects in material and workmanship for a period of 2 years from the date of the original purchase. It can be extended by one year if the user subscribes to website of myswap. The warranty only applies if the product is for household use. The warranty does not cover breakdowns due to normal wear and tear.

The manufacturer agrees to replace parts identified as defective by the designated distributor. The manufacturer does not accept responsibility for the replacement of the machine, in whole or in part, and/or ensuing damage.

### **The warranty does not cover breakdowns due to:**

- insufficient maintenance.
- abnormal assembly, adjustment or operations of the product.
- parts subject to normal wear and tear.

### **The warranty does not extend to:**

- shipping and packaging costs.
- using the tool for a purpose other than that for which it was designed.
- the use and maintenance of the machine done in a manner not described in the user manual.

Due to our policy of continuous product improvement, we reserve the right to alter or change specifications without notice. Consequently, the product may be different from the information contained therein, but a modification will be undertaken without notice if it is recognized as an improvement of the preceding characteristic.

### **READ THE MANUAL CAREFULLY BEFORE USING THE MACHINE.**

When ordering spare parts, please indicate the part number or code, you can find this in the spare parts list in this manual. Keep the purchase receipt; without it, the warranty is invalid. To help you with your product, we invite you to contact us by phone or via our website:

**+33 (0)9.70.75.30.30**

**<https://services.swap-europe.com/contact>**

You must create a "ticket" via the web platform.

- Register or create your account.
- Indicate the reference of the tool.
- Choose the subject of your request.
- Describe your problem.

Attach these files: invoice or sales receipt, photo of the identification plate (serial number), photo of the part you need (for example: pins on the transformer plug which are broken).



## 8. PRODUCT FAILURE

### WHAT TO DO IF MY MACHINE BREAKS DOWN?

#### **If you bought your product in a store:**

- Make sure that your machine is complete with all accessories supplied, and clean! If this is not the case, the repairer will refuse the machine.
- Go to the store with the complete machine and with the receipt or invoice.

#### **If you bought your product on a website:**

- Make sure that your machine is complete with all accessories supplied, and clean! If this is not the case, the repairer will refuse the machine.
- Create a SWAP-Europe service ticket on the site: <https://services.swap-europe.com> When making the request on SWAP-Europe, you must attach the invoice and the photo of the nameplate (serial number).

Contact the repair station to make sure it is available before dropping off the machine.

Go to the repair station with the complete machine packed, accompanied by the purchase invoice and the station support sheet downloadable after the service request is completed on the SWAP-Europe site

**Please keep your original packaging to allow for after-sales service returns or pack your machine with a similar cardboard box of the same dimensions.**

**For any question concerning our after-sales service you can make a request on our website <https://services.swap-europe.com>**

**Our hotline remains available at +33 (9) 70 75 30 30.**



## 9. WARRANTY EXCLUSIONS

### THE WARRANTY DOES NOT COVER:

- Start-up and setting up of the product.
- Damage resulting from normal wear and tear of the product.
- Damage resulting from improper use of the product.
- Damage resulting from assembly or start-up not in accordance with the user manual.
- Periodic and standard maintenance events.
- Actions of modification and dismantling that directly void the warranty.
- Products whose original authentication marking (brand, serial number) has been degraded, altered or withdrawn.
- Replacement of consumables.
- The use of non-original parts.
- Breakage of parts following impacts or projections.
- Accessories breakdowns.
- Defects and their consequences linked to any external cause.
- Loss of components and loss due to insufficient screwing.
- Cutting components and any damage related to the loosening of parts.
- Overload or overheating.
- Poor power supply quality: faulty voltage, voltage error, etc.
- Damages resulting from the deprivation of enjoyment of the product during the time necessary for repairs and more generally the costs related to the immobilization of the product.
- The costs of a second opinion established by a third party following an estimate by a SWAP-Europe repair station
- The use of a product which would show a defect or a breakage which was not the subject of an immediate report and/or repair with the services of SWAP-Europe.
- Deterioration linked to transport and storage\*.

\* In accordance with transport legislation, damage related to transport must be declared to carriers within 48 hours maximum after observation by registered letter with acknowledgement of receipt. This document is a supplement to your notice, a non-exhaustive list.

**Attention:** all orders must be checked in the presence of the delivery person. In case of refusal by the delivery person, it you must simply refuse the delivery and notify your refusal.

**Reminder:** the reserves do not exclude the notification by registered letter with acknowledgement within 72 hours.

#### **Information:**

Thermal devices must be wintered each season (service available on the SWAP-Europe site). Batteries must be charged before being stored.

# FEIDER



SODILOG SAS

4 RUE CURIE, CS 91617 68016 COLMAR CEDEX FRANCE

[www.sodilog.com](http://www.sodilog.com)

Made in PRC