

ORIGINAL INSTRUCTIONS



GASOLINE POLE PRUNER

RACS52PCS-A

INSTRUCTIONS MANUAL



WARNING: To reduce the risk of injury, the user must read and understand this manual before operating the tool.

RACING
ZI, 32 RUE ARISTIDE BERGES 31270 CUGNAUX, FRANCE



CONTENTS

1. INTENDED USE	3
2. SAFETY INSTRUCTIONS	4
3. THE TOOL	11
4. ASSEMBLY	14
5. FUEL TANK	19
6. UTILISATION	21
7. CARE AND MAINTENANCE	26
8. TRANSPORT AND STORAGE	28
9. TROUBLESHOOTING	31
10. EC DECLARATION OF CONFORMITY	32

1. INTENDED USE

We do everything in our power to ensure continuous improvement of our products. This is why the technical data and the data can be modified.

Pole pruner

Intended use / improper use

The pole pruner is exclusively intended for pruning trees and/or cutting small wood from the ground. Any other use is considered improper and will damage the tool.

The correct use also includes reading and observing the instructions for use at each use as well as observing the warnings fixed on the machine. Before and during use, it is imperative to check the blade to ensure that there is no mechanical damage. In case of necessary repairs, please contact your specialist dealer.

Only the use of spare parts approved by the manufacturer or original spare parts is permitted. If unauthorized or non-original spare parts are used, the user is liable for consequential injury to persons or property resulting in the manufacturer being deprived of all liability.

Residual risks

A certain residual risk that cannot be totally excluded still exists even if the tool is used in conformity. The type and design of the tool may represent the following potential hazards depending on the use made of it:

- Contact with sawdust
- Inhalation of sawdust particles
- Inhalation of exhaust gases
- Skin contact with oil / gasoline
- Inhalation of gasoline / oil vapors
- Contact with projected chain links
- Cutting of the fingers at the cutting chain
- Burning of fingers in contact with hot surfaces (exhaust etc.).

2. SAFETY INSTRUCTIONS

General safety instructions

If you feel an unpleasant sensation in the hands or if you see a coloring of the skin of your hands while using the machine, stop the work immediately. Have enough breaks when working. Failure to observe sufficient work breaks may result in hand and arm vibration syndrome.

It is thus necessary to assess this impact according to the work carried out or the use of the machine and to take breaks accordingly. This greatly reduces the impact on the user during the entire working period. Minimize your risk of vibration. Maintain this machine in accordance with the instructions in the operating instructions.

If the machine is used frequently or more regularly, we recommend that you contact your specialist dealer for anti-vibration accessories (handles) if necessary.

Avoid using the machine at temperatures of $t = 10^{\circ} \text{C}$ or lower. Develop a load plan to limit the impact of vibration on the user.

Read this manual carefully before operating the machine for the first time. In case of doubt about the connections or its use, please contact the manufacturer (specialist dealer).

In order to guarantee a high level of safety, the following instructions must be strictly adhered to. Warning!

To ensure safety at work with this pole pruner, it is essential to strictly follow the instructions and to take into account the safety, assembly and use information contained in this manual. Anyone using or performing maintenance work on the machine must be familiar with and familiar with these instructions in order to be aware of all possible risks. Prevent children, sick or impaired people from accessing the machine. As you stand in the work area, be aware of the presence of children. Observe local or regional safety precautions in your area. This also applies to all provisions relating to safety at the workplace and to health prevention in the workplace.

The manufacturer must not be held liable if the machine has been modified in an unauthorized manner or in such a way as to constitute ultimately damage.

Warning!

It is essential to observe the necessary safety instructions when using the machine. Observe the notes and notes given in the enclosed safety instructions.

1. Consider the nature of the area where the work is done. After starting the machine, it produces toxic exhaust gases. These gases are invisible and odorless. Therefore, it is imperative never to use the machine in closed or poorly ventilated spaces. During the cut, make sure you have good lighting. Provide stability when working on slopes or rough surfaces in the presence of moisture, snow or thaw.
2. Do not let unauthorized persons approach the machine. Visitors and spectators, mainly children, sick or weak people, should not be able to access the work area. Prevent other people from contacting the tool.
3. Take the necessary precautions when storing the tool. When the machine is not in use, it must be stored in a dry place, if possible elevated or protected, so as to prevent any access.
4. Always use the right tool for the jobs you want to do. In this context, for example, the use of a small tool or attachment should not be used for work requiring the use of a heavy tool. Only use the tool for the purpose for which it was designed.
5. Make sure to wear appropriate clothing. The clothes should be appropriate and do not interfere with your work. Wear integral clothing with rigid protections against cuts.
6. Use personal protective equipment. Wear non-slip safety shoes and snug clothing.
7. Wear safety glasses. Objects can be projected in the eyes.
8. Wear hearing protection. Wear personal protective equipment to protect your ears, such as hearing protection.
9. Protective gloves. Wear sturdy gloves. Leather gloves provide good protection.
10. Using the tool. Never work with an unsecured cutting tool. There is a risk of injury from projected objects.
11. Stay alert at all times. Be careful what you do. Use your common sense. Do not use the tool when you are tired. Never use the tool under the influence of alcohol, drugs or drugs that impair or reduce concentration.
12. Refilling the fuel tank. Before filling the fuel tank, it is imperative to always stop the engine. Open the tank lid carefully, so that any overpressure can be evacuated and fuel cannot escape from the tank. During operation of the tool, high temperatures develop in the machine housing. Therefore, it is imperative to let the machine cool down before filling the fuel tank. Otherwise, the fuel can ignite spontaneously which can cause burns. Filling the fuel tank means not filling the tank beyond the authorized limit. If fuel dries from the tank, it should be removed immediately before using the machine again. After filling the tank, check the tightness of the screwed connections to prevent them from coming off during work due to vibration.
13. Hours of work and breaks. After using the motorized machine for a long time, you may be susceptible to circulation problems in your hands. While you have the opportunity to extend the duration of use by wearing suitable gloves and taking breaks regularly. Take into account that the operating time of the motorized machine is shortened due to user discomfort due to poor circulation; too low outdoor temperature or excessive motor power of the machine during the works.
14. Pay attention to damaged components. Check the machine before using it. Are there any components damaged? When you detect minor damage to the machine, seriously ask yourself whether the machine can still be used properly and safely. Make sure that the orientation and adjustment of the moving components are correct. Are the different

components correctly adjusted to each other? Is any component damaged? Everything has been installed in the rules of art? Are all other conditions available to work properly at the location indicated? Unless otherwise stated and explicitly stated in these operating instructions, safety accessories, etc. damaged, must be repaired or replaced as soon as possible by authorized persons. Defective switches must be replaced by an authorized specialist dealer. Do not use the machine when it cannot be turned off or on by a switch. When repairs are required, please contact your nearest dealer.

15. Before carrying out any adjustment or maintenance operations, it is essential to always switch off the engine. This also applies to all work done at the cutting head. Remove the spark plug from the engine.

16. Only use approved components. Only use spare parts that are identical to those you replace during maintenance or repair. For this purpose, do not hesitate to seek advice from your authorized specialist dealer. Do not use multi-piece metal swivel chains and flail blades with this machine

17. When transporting and storing the tool, make sure the tool is secure; put the protection device on the blade and the tool during transport, storage, cleaning and maintenance.

18. To avoid fuel leakage, damage and injury, pay attention when handling and transporting the tool. Do not forget to put the protective device every time.

19. Do not use the appliance when you are tired, ill or under the influence of alcohol or drugs.

20. Use only the accessories and protections recommended by the manufacturer. Give your dealer a list of recommended accessories if necessary. Using parts not recommended by the manufacturer may result in injury, accidents, and tool malfunction.

21. Keep a good balance and balance when operating the tool. Stay firm on the ground so as not to fall. Do not lean excessively, do not put yourself in positions that could unbalance you and hurt you. Use the harness supplied with the tool.

22. Check regularly that the cutting elements stop when the machine is idling.

23. National regulations may restrict the use of the pruner.

24. Do not use the tool near power lines. There is a risk of danger and serious accidents.

25. Always have a good working position, stand up, and stay firmly on the ground. Hold the tool firmly.

26. Do not use the tool in unsafe operating positions; do not stand on a ladder.

27. The tool may be caught, blocked or malfunctioning during operation. When a danger is encountered, stop using the machine. Observe the problem; set the blockage if you are able or ask for help. When removing a blockage, wear protective equipment.

28. We recommend cutting branches by section.

29. There is a risk of being struck by fallen branches that have hit the ground or have bounced.

30. Keep a stable position and stay balanced during operation.

31. Always use the harness provided.

32. Clean and service before storing.

33. Check regularly that the cutting element stops when the machine is idling.

34. If you need to change the cutting accessories, contact your dealer or the manufacturer for a list of accessories that can be used with this tool. Do not use non-recommended accessories as they may cause malfunctions and accidents, breakdowns and damage.

35. Check the tool before and after each use. Maintenance of the tool should be done regularly, following the instructions given in this manual. Improper and / or incorrect maintenance can damage the tool and give poor work results.

Warning! The use of another cutting head or other accessories and extensions, even when explicitly advised, may constitute a risk of personal injury or property damage.

The machine must not be used for purposes other than intended. Any use deviating from these purposes must therefore be considered as unauthorized use. The user is solely responsible, thus releasing the manufacturer systematically from any liability, in case of bodily or material damage resulting from such unauthorized use.

The manufacturer's warranty is void if the machine it has been designed has been transformed or used in an unauthorized manner and such situation results in damage

Warning!

Even if the machine is used professionally, it is impossible to completely eliminate some residual risk. The type and design of the machine make it possible to establish the following potential risks:

- Contact with uncovered cutting head (cut wounds)
- Contact with the tool during operation (injuries by cuts)
- Hearing impairment in the absence of proper hearing protection. Development of toxic dusts / fumes when used in confined spaces (vomiting / nausea)













When using the pruner, it is imperative to use the pole


Emergency measures

Provide first aid based on the injury and seek medical attention as soon as possible.

Protect the injured person from other hazards and keep him calm.

Symbols on the machine

	<p>Wear a protective helmet, and ear and eyes protection.</p>	 <p>≤ 7500min⁻¹</p>	<p>Maximal rotation of speed of the spindle</p>
	<p>Wear protective gloves</p>	 <p>max. zulässige Drehzahl: 1400min</p>	<p>Allowed maximal rotation speed. This symbol indicates the orientation of the cutting teethes when the assembly</p>
	<p>Wear protective non-skid shoes</p>		<p>Pay attention to the risk associated with carbon monoxide</p>
 	<p>Read instructions manual</p>		<p>Warning! be careful of hot surfaces : risk of burning</p>
	<p>The fuel is highly flammable, do not place it near a flame or a fire</p>		<p>Keep hands and feet away from sharp accessories!</p>
		 <p>LWA 114 dB(A)</p>	<p>Sound power level: LWA : 114dB</p>

	<p>Do not use the pruner near cables, power lines or telephone lines. When using the pruner, keep a safe distance of 10 meters from overhead power lines</p>
---	--

In general, the machine has been designed for use in agriculture and forestry, gardening and landscaping, work in the forest or in a garden.

The manufacturer cannot be held liable for damage resulting from non-observance of the general instructions and the instructions contained in these operating instructions.

Residual risks and preventive measures

Mechanical risks

Risk	Description	Preventive measures
Cutting, injuries	cutting The sharp filament and cutting blades can cause serious injury. Ensure that no people or animals are in the work area.	Ensure that no people or animals are in the working area
Hanging	Cables and filaments can be caught by the cutting blade or the filament reel, which can damage the machine and cause injury. Remove all foreign objects from the area you want to mow before	Remove all foreign objects from the area you want to mow before starting work.
Shocks	Strong feedback shocks can occur when using the unit in dense bushes. When the knife remains blocked, violent shocks can be felt through the pole.	Do not penetrate too deep into dense bushes. Take your time and avoid the knife jamming.

Negligence

Risk	Description	Preventive
Negligence in the use of personal protective equipment	Negligence in the use of personal protective equipment may result in serious personal injury	Use the necessary protective equipment

Individual / Incorrect Behaviour		Be totally focused on your work
----------------------------------	--	---------------------------------

Residual risks from heat

Risk	Description	Preventive measures
Burns, frostbite	Contact with exhaust can cause burns	Allow the exhaust to cool after using

Residual risk from noise

Risk	Description	Preventive measures
Loss of hearing	Regular / prolonged use of the tool without the use of hearing protectors can cause loss of auditory acuity.	Always wear ear protectors.

Residual risks from others materials and substances

Risk	Description	Preventive measures
Contact aspiration	Exhaust gas may have a harmful effect	Only use the machine outdoors and in accordance with its intended purpose
Fire explosion	The mix of fuel is flammable	Do not smoke and manipulate fire near the tool and fuel

Risks from vibration

Risk	Description	Preventive measures
Vibration of the body	A prolonged use of the tool could have a negative effect on human health	Do some rests

Others risks

Risk	Description	Preventive measures
Projected objects	Stones and pieces of wood projected in the vicinity are likely to injure people or animals.	Ensure that no persons or animals are in the hazardous area and wear suitable protective clothing, hearing protection and a visor.
Sliding, stumbling and falling	On uneven floors, damage can be caused by stumbling	Be sure to always be on your support and wear non-slip shoes

Disposal / Recycling

Disposal instructions are indicated in the form of pictograms attached to the machine or packaging. The meaning of the various symbols is given in the chapter "Symbols attached to the machine".

Requirements to the user

Before using the machine, the user must read the instruction manual carefully

Qualification

The machine must be operated by a qualified person who has had special training with a specialist.

Minimum Age Required


Use of the machine is only permitted for persons aged 16 or older. This point does not apply to the use by young people in training, when they work with the machine as part of their vocational training with the aim of acquiring this know-how under the supervision of a trainer.

Special requirements to the user

- Before using the machine, the user must read the instruction manual carefully.
- The tool must be used by a qualified person who had training provided by a specialist.
- Use of the machine is only permitted for persons aged at least 16 years. This point does not apply to the use by young people in training when they work with the machine as part of their vocational training with the aim of acquiring this know-how under the supervision of a trainer.

3. The tool

Main unit



1. Device for installing the shoulder strap
2. Engine
3. Bottle for the oil mixture
4. Protection of the blade (pruner)
5. Assembly tools (wrenches and screwdrivers)
6. Pruner
7. Strap
8. handle
9. Power Switch
10. Fuel tank
11. Exhaust of gas
12. Choke control
13. Starter
14. Tank cap

Pole mounted pruner




- 1- Tube
- 2- Oil tank for lubrication
- 3- Cutting head

4. ASSEMBLY

NOTE: This model comes with a stretch tube. This tube must be installed on the fixing tube of the machine then the accessories will be installed on this extensible tube.

A) Main unit



Install the front handle as shown in the picture below. Be sure to orient the stem toward the hole. Do not fasten the screws until you have set the most comfortable working position with the straps. The front handle must be oriented as shown in the picture for "the motor and drive unit".



Accessories setting




- Loosen the clamping knob
- Connect the cutting blade to the machine tube (Make sure the lock is securely engaged in the mounting hole).
- Tighten the knob. Make sure the connection is secure.

Assembly of the chain guide and the cutting chain:

Remove the safety screw and remove the guard.




Place the chain guide so that the safety pin on the chain engages in the chain's teeth. Make sure that the direction of movement of the cutting chain is correct. Install the chain guard and tighten the fastening screw.



Adjusting the chain tension


The chain must not have too much clearance, but it must be possible to lift the chain a few millimeters from the guide rail.

- Loosen the fixing screw (1).
- Slightly lift the end of the chain guide
- Check the cutting chain for ease of operation by turning it manually.
- Adjust the tension of the chain by means of the screw for adjusting the tension of the chain (4) so that the chain can be lifted a few millimeters from the center of the guide rail.
- Secure the safety screw (1).



Use of the pole pruner

Never use the tool at an angle of more than 60 °. The correct operation of the pruner is not impaired at angles greater than 60 °, but the risk of injury increases due to sudden drops of branches. Pay attention to the floor in front of you when using the appliance. This allows you to avoid tripping over branches on the ground. Never use the saw without oil. Use a biodegradable chain oil. The pruning machine uses a low rebound chain. In addition, special attention has been paid to the construction of the device to prevent the smallest possible rebounds given the technical conditions given. Nevertheless, a slight rebound can not be ruled out by using the upper cutting blade. Expect a rebound when using this side of the blade or when the top of the blade comes into contact with another branch. The device should always be used with both hands. The thin branches can be cut at once. To prevent a branch from splitting or bending, it is advisable to slice it end to end. When slitting longer branches, the branch should be cut from the bottom. First cut the branch from below at a point away from where you want to saw the branch. The notch must have a depth between one third and one half the thickness of the branch. This prevents the branch from breaking when you cut it from the top a little further away from the trunk. To finish, saw the stump by making a straight cut. If you wish, you can seal the cut using a suitable product.



Installation of the harness

The shoulder strap is equipped with an emergency release mechanism. To detach the machine from the shoulder strap in emergency situations, follow the instructions described below.

WARNING

Check the emergency release mechanism BEFORE operating the machine.

Be sure to hold the machine when operating the emergency release mechanism.

When holding the machine firmly with your right hand, press both sides of the belt buckle.

5. FILLING TANK

Warning: Gasoline is highly flammable. Keep the fuel in specially designed cans.

- Only fill the tank outside and do not smoke during the operation.
- Fill the tank before starting the engine. Never remove the fuel tank cap, add fuel while the engine is still running, or while the engine is still warm.
- Avoid overfilling the tank: When excess fuel has escaped, do not attempt to start the engine, but move the machine away and avoid any sources of ignition in the vicinity until the fuel vapors have dissipated.
- Fully tighten all fuel filler caps and cans.
- Fill the tank on the floor.
- The engine must be started at a distance of at least 3 meters from where the fuel tank has been filled.
- Switch off the engine before adding fuel. Shake the mixture thoroughly before filling the tank.
- Store gasoline in tanks specially designed for this purpose.
- Fill the fuel tank of your appliance outdoors and avoid smoking during work.
- Fill the tank before starting the engine. Never open the fuel tank cap or fill fuel tank while the engine is running or the engine is still hot.
- Avoid spilling gasoline: When gasoline is spilled, do not start the machine and move it away from where the gasoline has spilled to avoid possible sources of fire.
- Screw all caps and tank cover carefully

Gasoline is highly flammable. Do not smoke and avoid sparks or open flames near the fuel. Turn the engine off and allow it to cool before filling the fuel tank. Filling must be done externally, ideally on the bare ground. Leave at least 3 meters from where you filled the tank to start the engine.

The engine requires oil specially adapted for two-stroke engines with an air cooling system. Use quality oil enriched with corrosion-inhibiting products explicitly provided for two-stroke engines with an air cooling system (JASO FC or ISOEGC).

Do not use BIA or TCW OIL (suitable for 2-stroke engines equipped with a water cooling system).

SUGGESTED PROPORTIONS: GASOLINE 40: OIL 1

Exhaust emissions are regulated by the basic technical characteristics of the engine and its components (carburation, adjustment of spark plugs, control of exhaust opening and closing times) in the absence of accessories or a catalyst during combustion.

- These motors are designed for use with unleaded gasoline.
- Always use gasoline with a minimum octane rating of 90RON.
- Using gasoline with a lower octane rating may cause an increase in engine temperature, causing problems with the engine, including seizure.
- Using unleaded gasoline prevents unnecessary pollution in the interests of your health and the protection of the environment.
- Using gasoline or oil of lesser quality can damage seal rings, ducts or fuel tank.

Prepare the mixture

IMPORTANT

MIX THE MIXTURE CAREFULLY.

- a. Measure the fuel and oil needed for the fuel mixture.
- b. Pour a little gasoline into a clean container provided for this purpose.
- c. Add all the oil before stirring the can.
- d. Add remaining gasoline and shake the can for at least 1 minute. Certain oils mix with difficulty because of the substances they contain. Sufficient agitation of the mixture is essential to ensure proper operation over the life and power of the engine. If your fuel mixture is not stirred sufficiently, the poor and inadequate mixture may increase the risk of seizure.
- e. Identify the can by locating it with a distinctive emblem in order to always know what is there.
- f. Indicate the substances contained and the proportions of the mixture.

Filling the tank

- a. Unscrew the tank cap. Place the tank cap in a clean, dust-free place.
- b. Fill the tank to 80% of its capacity.
- c. Screw the fuel cap back on. Clean the fuel tank cap and the area around after filling the fuel tank. Eliminate overfill of fuel mixture by rubbing.

NOTE

When filling, avoid:

- **OIL-FREE FUEL (PURE FUEL) - This can quickly cause serious damage to the interior of the engine components.**
- **GASOHOL - may cause deformation of rubber or plastic parts and cause engine lubrication to stop.**
- **OIL FOR 4-TIME ENGINES - causes clogging of the spark plug, clogs the exhaust channel or leads to seizure.**

Fuel mixtures stored for more than one month may, if used, clog the carburetor and cause the engine to malfunction.


If the unit is to be stored for an extended period of time, the tank must be cleaned after being emptied. Leave the engine running to remove the remaining fuel from the carburetor.

Observe local regulations when disposing of used containers.

6. UTILISATION


WARNING Fill the fuel tank before tightening the fuel tank cover.

Put the machine on a level, solid floor. Keep the cutting head away from the ground and away from surrounding objects (Fig.5).



3. Press the priming bulb 5 to 8 times until fuel flows through the clear hose.

4. Position the choke in the closed position.



5. Set the STOP switch to position "I". Make sure the cutting head is clear. Store the machine on a level, solid floor.

6. Keep the machine on the ground safely and then pull the starter until the engine starts

WARNING

The machine is equipped with a centrifugal clutch system.

When starting the engine, place the machine on a level, clean floor and hold it firmly to prevent the sharp components or the throttle lever from coming into contact with any objects when the engine is started.

IMPORTANT

- **Avoid pulling the starter to the end or return the cable by suddenly releasing its handle. This can cause the engine to fail.**

- **Position the choke in the "open" position and restart the engine.**
- **Let the engine warm up a few minutes before starting work.**

NOTE

- When restarting the engine directly after stopping it, keep the choke switch in the "open" position.
- Overheating complicates engine starting due to overfilling of fuel. If the engine does not start after several attempts, open the starter and press the starter several times, or remove and dry the spark plug.

B) Stop the engine

- Release the throttle lever and let the engine run for about 30 seconds.
- Set the stop switch to the STOP position.

IMPORTANT

- **Except in case of emergency, do not switch off the engine by pulling on the choke lever.**
- **If the engine does not stop by pressing the stop switch, move the choke to the closed position.**

C) Safety instructions of use

Never use this tool when standing on a ladder!

Always work on a hard and stable floor!

Only use the machine after reading the operating instructions carefully.

Observe all safety instructions in this manual.

Act responsibly towards others.

Avoid bouncing. Rebounds can cause serious injury. The pruning machine should not be used when standing on a ladder or if someone else is assisting you is not stable on its support. You may lose control of the saw and experience severe injuries. If circumstances require the use of heavier / larger machines, ask a specialist for assistance.

Caution:

1. Pay attention to falling branches.
2. The boom must be installed

FUEL WARNING

Gasoline is highly flammable. Do not smoke and be careful to avoid sparks or open flames near fuel. Turn the engine off and allow it to cool before refueling. Filling must be done externally, ideally on the bare ground. Leave at least 3 meters from where you filled the tank to start the engine.

The engine needs oil specially adapted for two-stroke engines with an air cooling system. Use quality oil enriched with corrosion-inhibiting products explicitly provided for two-stroke engines with an air cooling system (JASO FC or ISOEGC).

Do not use BIA or TCW OIL (suitable for 2-stroke engines equipped with a water cooling system)

SUGGESTED PROPORTIONS: GASOLINE 40: OIL 1

- Exhaust emissions are regulated by the basic technical characteristics of the engine and its components (carburation, spark plug adjustment, exhaust opening and closing control) in the absence of accessories or A catalyst during combustion
- These motors are designed to operate with unleaded gasoline.
- Always use petrol with a minimum octane rating of 90RON.
- Using gasoline with a lower octane rating may result in an increase in engine temperature, causing problems with the engine, including seizure.
- Using unleaded gasoline prevents unnecessary pollution in the interests of your health and the protection of the environment.
- Using gasoline or oil of lesser quality can damage seal rings, ducts or fuel tank.

HOW TO PREPARE YOUR OIL-FUEL MIXTURE

IMPORTANT

SHAKE CAREFULLY THE PREPARED MIXTURE

1. Measure the fuel and oil required for the fuel mixture
2. Pour a little gasoline into a clean container provided for this purpose.
3. Add all the oil before stirring the can.
4. Add remaining gasoline and shake the can for at least 1 minute. Certain oils mix only with difficulty because of the substances they contain. Stirring the mixture sufficiently is essential to ensure proper operation over the life and power of the engine. If your fuel mixture is not stirred sufficiently, the poor and inadequate mixture may increase the risk of seizure.
5. Identify the can by locating it with a distinctive emblem to always know what is in it
6. Indicate the substances contained and the proportions of the mixture.

FILLING THE DISCONNECT TANK

1. Unscrew the tank cap. Place the fuel cap in a clean, dust-free place.
2. Fill the tank to 80% of its capacity.
3. Screw the fuel cap back on. Clean the fuel tank cap and area around after filling the fuel tank. Eliminate overflow of fuel mixture by rubbing.

WARNING

1. Fill the tank on the floor.
2. The engine must be started at a distance of at least 3 meters from where the fuel tank has been filled.
3. Switch off the engine before adding fuel. Shake the mixture thoroughly before filling the tank.

Warning: Gasoline is highly flammable. Therefore, it is imperative to take the following precautions:

- 1) Store gasoline in tanks specially designed for this purpose.
- 2) Fill the fuel tank of your appliance outdoors and avoid smoking during work.
- 3) Fill the tank before starting the engine. Never open the fuel tank cap or fill fuel while the engine is running or the engine is still hot.

Avoid spilling gasoline: When gasoline is spilled, it is important not to start the machine and move it away from the place where the gasoline has spilled to avoid possible sources of fire.

Screw all caps and tank cover carefully

IN THE INTEREST OF YOUR ENGINE, AVOID:

1. OIL-FREE FUEL (PURE FUEL) - This can quickly cause serious damage to the interior of

the engine components.

2. GASOHOL - may cause deformation of rubber or plastic parts and cause engine lubrication to stop.
3. OIL FOR 4-TIME ENGINES - causes clogging of the spark plug, clogs the exhaust channel or leads to seizure.
4. Fuel mixtures stored for more than one month may, if used, clog the carburetor and cause the engine to malfunction.
5. If the unit is to be stored for a long period of time, the tank must be cleaned after being emptied. Leave the engine running to remove the remaining fuel from the carburetor.
6. Observe local regulations when disposing of used containers.

7. CARE AND MAINTENANCE

Warning! The following instructions refer to normal operating conditions. In the presence of more difficult working conditions or when the work is carried out for a prolonged period, it is necessary to reduce the indicated intervals.

After work, it is essential to always check the entire machine and clean it.

Regular checks and maintenance:

- **Check the air filter (to be cleaned if necessary)**
- **Check spark plugs (replace if necessary)**
- **The correct operation and quality of cutting accessory.**

Always switch the drive unit off when performing any maintenance or repair work.

Check for loose fasteners, fuel leaks and damaged parts (e.g. cracks in the cutting blade).

A) Safety and Maintenance Instructions


The machine may only be used if it is serviced and maintained regularly. Insufficient maintenance or maintenance can lead to emergencies and unforeseen accidents.

Repairs should only be carried out by authorized specialists with the necessary technical knowledge. Interventions by non-specialists may damage the machine or be hazardous to safety.

Follow the instructions below:

- Ensure that all nuts, bolts and screws are tightened to ensure that the machine meets all safety conditions
- Never store the machine with fuel remaining in the tank in a building where gasoline vapors may come in contact with flames or sparks.
- Allow the engine to cool before storing it in an enclosed area.
- To reduce the risk of fire, remove grease, grease and grease from the engine, muffler, battery and gasoline storage area.
- Replace worn or damaged components.
- When the fuel tank is to be emptied, do so outdoors.
- Do not attempt to repair the machine unless authorized to do so.
- Use only spare parts and accessories recommended by the manufacturer.

B) Maintenance plan



C) Sharpening

Sharpening shall be done by a qualified service or by an experimented person who must follow the below instructions. Do not perform sharpening if you do not have the knowledge to do it.

Be careful to file all cutters to the specified angles and to the same length, as fast cutting can be obtained only when all cutters are uniform.

Tighten the chain tension enough that the chain does not wobble. Do all of your filing at the midpoint of the bar. Wear gloves for protection.

Use a round file and holder.

Keep the file level with the top plate of the tooth. Do not let the file dip or rock.

Using light but firm pressure, stroke towards the front corner of the tooth. Lift file away from the steel on each return stroke.

Put a few firm strokes on every tooth. File all left hand cutters in one direction. Then move to the other side and file the right hand cutters in the opposite direction. Occasionally remove filings from the file with a wire brush.

8. TRANSPORT AND STORAGE

When the machine is not used for an extended period of time (1 month), the following measures should be taken:

- Empty the oil and fuel tank.
- Disassemble and clean the thread spool and cutting blade.
- Dry the spool of wire and the cutting blade using a cloth.
- Rub the outside of the machine using a soft, damp cloth.
- Store the machine in an enclosed and well ventilated place. Keep the machine so that it is not accessible to children.
- Store the machine in a dry place.
- The pruning machine must be properly packaged to prevent cuts.
- Use the baffles on cutting accessories with a metal knife.

9. TECHNICAL INFORMATION

Engine information	
Type of engine	RY1E44F-5
Volume of the fuel tank	1200 cm ³
Max engine speed	Max. 9000 min ⁻¹
Engine idling speed	3100±400 min ⁻¹
Engine speed with clutch engages	3900/4700 min ⁻¹
Engine displacement	52cm ³

Maximal power	1,75 kW 7000 min ⁻¹
Unit without cutting attachment, empty	7,5 kg
Volume of oil tank	140 cm ³
Cutting length	300/260 mm
Max rotational frequency of the spindle	8800 min ⁻¹
Vibration ahv	Ahveq left: 8,342 m/s ² ; K=1,5 m/s ² Ahveq right: 8,505 m/s ² ; K=1,5 m/s ²
Noise emission	Sound pressure level: L _{pA, eq} =105,25 dB(A); K=3 dB(A) Sound power level : L _{wA, av} =113,68 dB(A) ; K=3 dB(A) Guarantee sound power level : 114 dB(A)

10. TROUBLESHOOTING

Problems	Causes	Resolutions
The tool cannot be started	The starting process is not followed	Follow the instructions of use of this manual
	Spark plug dirty or moist	Clean the spark plug or replace it by a new one
	Incorrect carburettor adjustment	Contact your dealer or contact SWAP
The tool starts but no in a full power	Non correct setting of the starter	Open the starter
	Air filter is dirty	Clean the air filter
	Incorrect carburettor	Contact your dealer or contact
The engine cannot reach its maximal power	Non correct gap between the electrode and the spark plug	Clean the spark plug and adjust the gap between the electrodes or replace them with a new one
	Incorrect carburettor adjustment	Contact your dealer or contact SWAP
The engine generate of lot of smoke	Incorrect mix of the tank	Do a correct mix of the fuel (see the corresponding chapter)
	Incorrect carburettor adjustment	Contact your dealer or contact SWAP

11. Declaration of conformity



RACING

ZI, 32, rue Aristide Bergès – 31270 Cugnaux - France

Declare that the tool: **GASOLINE POLE PRUNER**

Ref: RAC52PCS-A

Serial number: 20180806390-20180807541

Is in conformity with the Directive Machine 2006/42/EC and the national regulation transposing it

Also in conformity with the following European regulation:

Machine Directive 2006/42/EC

EMC Directive 2014/30/EU

Emission Directive 2010/26/EU

Noise Directive 2000/14/EC Annex V and 2005/88/EC
Measured sound pressure level 113,68 dB (A) K=3 dB(A)
Guarantee sound power level: 114 dB (A)

Is also in conformity with the following standards:

EN ISO11680-1:2011

EN ISO 14982:2009

Notified body 1067

AVTECH House, Arkle Avenue, Stanley Green Trading Estate, Handforth, Cheshire SK9 3RW

T: +44 (0)161 486 3737 F: +44 (0)161 486 3747 W: www.avtechnology.co.uk

Responsible of the technical file: Mr Olivier Patriarca

Cugnaux, 13/08/2018

A handwritten signature in black ink, appearing to read 'Philippe MARIE', with a stylized flourish at the end.

Philippe MARIE / PDG